

## USB 16/32COM-RM

### USB Bus

Compliance	USB 1.0/1.1 compliant, USB 2.0 & 3.0 compatible
Speed	480Mbps, hi-speed USB
FIFO	128 byte transmit 384 byte receive

### Serial Interface

Interface	RS-232
Number of Ports	32
Connector	32 Port RJ45, 32 cables RJ45 to DB9 male included (150 cm) 16 Port DB9
Max. Speed	921.6kbps for transmit & receive
RS-232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
Protection	10kV ESD protection for all signals

### Serial Communication Parameters

Data Bits	5, 6, 7, 8
Parity	None, odd, even, mark, space
Stop Bit	1, 1.5, 2
Flow Control	Hardware (RTS, CTS), XON/XOFF

### Power

Power Input	Internal power supply, 100-240V AC
-------------	------------------------------------

Casing

SECC metal rackmount chassis, also suitable for DIN rail mounting

(rackmount brackets included)

### Environmental

Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20°C to 75°C (-4°F to 167°F)
Operating Humidity	5% to 95% RH
Safety Approvals	CE, FCC



Gleneagles House, 31 Riverside Road, West Moors, BH22 0LG

Tel: 01202 861512

[www.roalan.com](http://www.roalan.com)

Registered in England No. 04591605